

ROCKINSUL BUILDING ROLL



Now also
with
ALG


Thickness : 40-100 mm
Dimensions : 1.1-1.2 m (width), 5-10 m (length)
Facing & covering : FSK, ALG & Kraft Paper
Application Fields : Thermal and acoustic insulation of metal buildings (over and under roof purlins, walls), porta-cabins, partition wells, and roofs (false ceiling overlay).




TUFFINSUL SLABS




Thickness : 25-150 mm
Dimensions : 0.6 m (width), 1 m (length)
Facing & covering : Unfaced
Application Fields : Thermal insulation where extra rigidity is required such as sandwich panels, roof and flooring applications.



TUFFINSUL LAMELLA BATS



Thickness : 25-118 mm
Dimensions : 100-110 mm (width), 0.92-1.2 m (length)
Facing & covering : Unfaced
Application Fields : Extra rigid thermal and fire-safely insulation used as core material for sandwich panels.



ROCKINSUL ACOUSTIC 6



Thickness : 50-100 mm
Dimensions : 0.6 m (width), 1 m (length)
Facing & covering : Unfaced
Application Fields : Acoustic insulation ideally suited for partition walls.



ROCKINSUL ACOUSTIC THERMAL INSULATION BOARD (ATIB)



Thickness : 20-30 mm
Dimensions : 590 x 590 mm
Facing & covering : FSK (one side), BGT (other side) (encapsulated solution)
Application Fields : Acoustic insulation for false ceiling applications in airports, hospitals, entertainment malls, hospitals and commercial complexes.



ROCKINSUL LRB MATTRESSES

Thickness : 25-100 mm
Dimensions : 1.22 m (width), 1.52-4 m (length)
Facing & covering : Galvanized steel or stainless hexagonal wire
Application Fields : netting (mesh) Thermal insulator of high-temperature equipment (boilers, fluid storage tanks, etc) and pipelines upto 750°C

**ROCKINSUL RB SLABS**

Now also
with
ALG

Thickness : 25-150 mm
Dimensions : 0.6 m (width), 1-2 m (length)
Facing & covering : Unfaced, FSK, ALG and BGT
Application Fields : Thermal and acoustic insulation in residential and commercial buildings, as well as industrial applications, especially where fire hour rating (fire safety) is required.

**ROCKINSUL PIPE SECTIONS**

Thickness : 25-100 mm
Dimensions : 1/2"-14" (Nom. Bore)
Facing & covering : Unfaced, FSK & ALG
Application Fields : Thermal insulation of pipe work

**ROCKINSUL LOOSEWOOL**

Thickness : NA
Dimensions : NA
Facing & covering : NA
Application Fields : Thermal insulation for in-fill around pipe bundles and for brake/ clutch pads.

Address:

Rockwool India Limited,
4th Floor, B Block, Laxmi Cybercity,
Kondapur, Hyderabad - 84 AP.

Phone: 040 - 30408650

Website: www.rockwoolindia.com

Email: customersupport@rockwoolindia.com